



Panel Uses & Information:

Designed for use in single-layer floor construction beneath carpet and pad. The span rating is stamped on each panel. Glue-nailing is recommended for Sturd-I-floor panels, though panels maybe nailed only. Install with smooth side up. Stagger panel end joists. Spacing of 1/8" is recommended at panel ends and edges, unless otherwise indicated.

Sturd-I-Floor also features APA Quick-Fit™ Tongue & Groove design so panels fit together quickly and easily, for even faster installations.

Panel Size:

Nominal 4' X 8' (sized for spacing)

Length & Width (minimum):

Length	7'-11 7/8"	2.435 m
Width, <i>Square Edge</i>	3'-11 7/8"	1.216 m
Width, <i>Tongue & Groove</i>	3'-11 1/2"	1.206 m



Trademark examples courtesy of APA-The Engineered Wood Association.

Prescriptive Specifications:

Thickness	Span Rating	Minimum Nbr Plies Layers	Building Code Performance Categories
19/32 PERF CAT	20 o.c.	4-3	0.563" – 0.625" (14.29mm – 15.88mm)
23/32 PERF CAT	24 o.c.	4-3	0.688" – 0.750" (17.46mm – 19.05mm)
1 1/8 PERF CAT	48 o.c.	7-5 or 7-7	1.069" – 1.181" (27.15mm – 30.00mm)

Construction and Characteristics:

Length/Width Tolerance: +0", -1/16" (+0, -1.6mm)

Straightness Tolerance: ±1/16" (±1.6mm)

Squareness Tolerance: ±1/8" (3.2mm)

Primary Species: Southern Yellow Pine

Testing Agency: APA-The Engineered Wood Association

Classification: Exposure 1 – Plywood suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.

Flame Spread Rating: 76-200 (tested in accordance with ASTM E84), smoke developed index < 200

Code Fire Classification: Class III or C

Building Code Compliance: PS 1-09

HUD-UM-40, APA V-600 for Exposure 1, APA V-611 for Exterior panels

Product Support and Frequently Asked Questions:

Please contact APA's Product Support Help Desk at (253) 620-7400; e-mail: help@apawood.org; or through the APA website at www.apawood.org



International:

Exempt from ISPM 15 regulations (*ISPM 15: International Standards for Phytosanitary Measures*)

Formaldehyde Emissions:

Exempt from testing or monitoring HUD in the *Manufactured Home Construction and Safety Standards*.

PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)*

Manufacturing Locations:

Location	Mill Number	Zip Code	Harvest Radius
Oakdale, LA	APA 219	71463	60 miles
Florien, LA	APA 221	71429	70 miles

Forestry Certification:




Made from Sustainable Forestry Initiative® (SFI®) certified responsible wood sources.



Made from PEFC certified responsible wood sources.

FIGURE 1
APA RATED STURD-I-FLOOR 16, 20, AND 24 oc



Figures 1-3 courtesy of APA-The Engineered Wood Association

FIGURE 2
APA RATED STURD-I-FLOOR 32 oc AND 48 oc (Over Supports 32" o.c.)





FIGURE 3
APA RATED STURD-I-FLOOR 48 oc (Over Supports 48" o.c.)



Product Support and Frequently Asked Questions:

Please contact APA's Product Support Help Desk at (253) 620-7400; e-mail: help@apawood.org; or through the APA website at www.apawood.org